



**CORROSION
RESISTANT**

Centrifugal Pump

**NON CLOG HORIZONTAL
SELF PRIMING PUMP**

Contact Us

-  +91- 44-4301 2183 / +91-7200627289
-  sales@neweraengineers.com
-  No.96-A, TTK Road,, Alwarpet, Chennai,
Tamil Nadu 600018,INDIA.

NON CLOG HORIZONTAL SELF PRIMING PUMP

The pump is suitable for transferring liquids clean or polluted in nature and they can be used in applications requiring a self priming pump with a negative suction of upto 7.5 mtr such as draining building, pond, ditches and swimming pools. These are the go to pumps for agricultural uses as well as sewage plants.



About Pump

Features

- Easy Back Pull Out Design
- Designed with minimum downtime in mind
- Hasslefree installation
- Zero Leakage Design
- Improved and efficient Impeller Designs
- Efficient and high capacity in a compact design
- Space Saving and Practical Design
- Various Mechanical Sealing options available

M.O.C

- CI
- Bronze
- Gun Metal
- Stainless Steel and Other Alloys

Specifications

- Capacity : 75 M3 / hr.
- Head : up to 35 mtrs.
- Suction Head : up to 7.5 mtr.
- Max. Solid Hand Size : up to 25 mm
- Viscosity : up to 100 mm² / sec.


Applications

- Agricultural Usage
- Building Water Transfer
- Dewatering in Ships
- Dyes and Intermediate Industries
- Effluent Treatment Plants
- Industrial Usage
- Marine Applications
- Petroleum Industries
- Sewage Treatment Plants
- Swimming Pools


Installations




Self Priming



Drum Transfer



Positive Suction Head



Twin Suction Manifold